

# MicroPro+++

**A unique bacterial laden solid, combining a high bacterial count with slow release technology.**

## Overview

**MicroPro+++** slowly dissolves in your high organic load environment constantly releasing Bacillus spores. Our safe, all-natural bacteria, are present in high numbers to ensure effective degradation of accumulated organic matter in a wide range of environments.

**MicroPro+++** gradually dissolves over a 30 to 90-day period allowing for continuous treatment and degradation of waste. Our proprietary bacteria reduce odors, sludge, fats, oils and grease build ups. The dissolution rate depends on the flow rate of water across the cylinder.

## Advantages of MicroPro+++

- **Greatly reduces labor time**
- **Reduces hydrogen sulfide (H<sub>2</sub>S)**
- **Breaks down fat & grease build-up**
- **Eliminates malodors at their source**
- **Degrades a wide range of complex organics**
- **Enhances BOD/COD removal**
- **Cost effective & easy to use**
- **Increases system efficiency**
- **Contains no chemicals**
- **Changes biomass dynamics**

## An organic, all natural and safe way to recycle

### *Aquaculture*

Use in nursery tanks, hatchery tanks, aerated earthen and lined ponds, settling ponds and lagoons, processing plant wastes, etc.

### Directions:

Suspend **MicroPro+++** block in the water column close to where the water is coming into the pond. Active, moving water is essential. Water flow rates determine the rate at which the block will dissolve and how long it will last.

### Degradation flow rates when using MicroPro+++\*

25 KGD – 75 KGD    2 lb block

75 KGD – 250 KGD    5 lb block

250 KGD – 1MGD    10 lb block

1MGD+    30 lb block

KGD = Thousand Gallons a Day


MGD = Million Gallons a Day

\*Degradation rates depend on the water flow rates

AquaInTech Inc.  
16825 48<sup>th</sup> Ave W. Suite 322  
Lynnwood, WA 98037 USA

Tel: 425-787-5218  
Email: [sgnewm@aquain-tech.com](mailto:sgnewm@aquain-tech.com)  
URL: [www.aquain-tech.com](http://www.aquain-tech.com),  
[www.bioremediationaquaculture.com](http://www.bioremediationaquaculture.com)

C: 425-239-7682



# MicroPro+++

## Application

Organic waste in higher flow wastewater treatment systems with active water movement.

## Bacteria Count

4 billion CFU/gram

## Bacteria Type

Bacillus spore blend

## Typical Properties

Appearance – red solid form – cylinder  
Fragrance – mild earthy shelf life – 24 mo/u.o.c.

## Performance Properties

Effective pH range – 5.0-9.5 Temp Range - 45-120°F (5 - 50°C)

## Available Sizes

2, 5, 10. and 30 pound